



Totally Carpet Specs

Style Name	<u>Activity</u>
Style Number	1007
Pattern Repeat	Random Width x None Length
Tufted Yarn Weight	30 oz
Gauge	1/10
Construction	Enhanced Loop
Face Yarn	100 % Solution Dyed Nylon
Yarn Spec	Twisted & heatset for high performance
Tufts per Sq. Inch	140 (Gauge x Stitch Rate x Tufts/Stitch)
Pile Height	0.15
Primary Backing	4 oz Woven Polypropylene
Secondary Backing	High Performance Backing System with 18x5 Lino ActionBac
Tile Backing	Vinyl composite with recycled content
Width Broadloom	12'
Tile Size	24" x 24"
Post Installation Protection	Plastic protection is prohibited. It causes discoloration and accelerated soiling. Craft paper, corrugated box material or masonite are recommended.
Treatments	Commercial carpet soil protection & static control
Broadloom Adhesive	Totally Premium Broadloom Adhesive
Tile Adhesive	Totally Premium Tile Adhesive
Flammability	Passes Class 1 (ASTM E-648)
Electrostatic Propensity	Passes AATCC - 134 @ 3.5 KV or less
Dye Lot Size	Unlimited
Custom Colors & Weight	Please Inquire
Origin	Made in USA
LEED	Contributes to Leed Credits
CRI	Green Label Plus
Warranty	Tile: limited lifetime warranty. Broadloom: 10 year limited warranty