

Totally LVT Specs

Style Name	LiVe iT Up
Style Number	1046
Construction	Luxury Vinyl Tile with Beveled Edges
Plank Size	12" x 18" (305 mm x 457 mm)
Total Thickness	0.096" (2.5 mm)
Wear Layer Thickness	0.020" (0.51 mm)
Pieces Per Carton	18
Coverage per Carton 4 x 36	27 sq. ft
Static Load Limit (ASTM 970)	(Modified @ 1000 PSI): Pass

Totally LVT Testing

ASTM F-1700 (Standard Spec for Solid Vinyl Floor Tile)	Class III, Type B
ASTM F-1514 (Heat Stability)	Passes
ASTM F-925 (Stain & Chemical Stability)	Passes
ASTM-E-662 (N.B.S. Smoke Chamber)	< 450 - Passes
ASTM-E-648 (Flooring Radiant Panel)	Bfl-s1 Class 1
Static Coefficient of Friction	Meets or exceeds ADA guidelines

Totally LVT Environmental

Rapid Renewable Content	3% Minimum Pre-Consumer
FloorScore	CDPS 1350
ISO 9001, ISO 14001	Registered Manufacturing Facilities
Manufacture Location	Georgia, USA

Totally LVT Warranty

Limited 10 Year Commercial Warranty
Limited 10 Year *TOTALLY SHIELD Finish Warranty

*TOTALLY SHIELD: Eliminates the need for polish over a period of time depending on the amount of foot traffic providing appearance retention, cleanability, durability, and slip retardance

Totally LVT Installation

Required Adhesive, Pourous Sub Floor	373
Required Adhesive, Pourous and Non-Pourous Substrates	PSA
Required Adhesive, Non-Pourous Subfloor	Universal 2-part Adhesive*

*Required for use under hospital beds or where high performance is needed

