



Totally Carpet Specs

Style Name	Totally For All Too
Style Number	1263, 1363
Pattern Repeat	9.6" W x 6" L
Tufted Yarn Weight	15 oz
Gauge	1/10
Construction	Sheared Loop
Face Yarn	100% Solution Dyed Nylon
Yarn Spec	Twisted & Heatset For High Performance.
Tufts per Sq. Inch	100 (Gauge x Stitch Rate x Tufts/Stitch)
Pile Height	0.109
Primary Backing	4 oz Woven Polypropylene
Secondary Backing	High Performance Backing System with 18x5 Lino ActionBac
Tile Backing	Vinyl composite with recycled content
Width Broadloom	12'
Tile Size	24" x 24"
Treatments	Commercial carpet soil & static control
Post Installation Protection	Plastic protection is prohibited. It causes discoloration and accelerated soiling. Craft paper, corrugated box material or masonite are recommended.
Broadloom Adhesive	Totally Premium Broadloom Adhesive
Tile Adhesive	Totally Premium Tile Adhesive
Flammability	Passes Class 1 (ASTM E-648)
Electrostatic Propensity	Passes AATCC - 134 @ 3.5 KV or less
Dye Lot Size	Unlimited
Custom Color & Weight	Please Inquire
Origin	Made in USA
LEED	Contributes to Leed Credits
CRI	Green Label Plus
Warranty	Tile: Limited lifetime warranty Broadloom: 10 year limited warranty