



## Totally Carpet Specs

|                              |  |
|------------------------------|--|
| Style Name                   | <u>Stritex</u>   |
| Style Number                 | 1004   |
| Pattern Repeat               | 3.5" W x None  |
| Tufted Yarn Weight           | 29 oz  |
| Gauge                        | 1/10   |
| Construction                 | Tip Sheared Enhanced Loop  |
| Face Yarn                    | 100% Solution Dyed Nylon   |
| Yarn Spec                    | Twisted & heatset for high performance   |
| Tufts per Sq. Inch           | 132.5 (Gauge x Stitch Rate x Tufts/Stitch)   |
| Pile Height                  | 0.149  |
| Primary Backing              | 4 oz Woven Polypropylene   |
| Secondary Backing            | High Performance Backing System with 18x5 Lino ActionBac   |
| Tile Backing                 | Vinyl composite with recycled content  |
| Width Broadloom              | 12'  |
| Tile Size                    | 24" x 24"  |
| Post Installation Protection | Plastic protection is prohibited. It causes discoloration and accelerated soiling. Craft paper, corrugated box material or masonite are recommended. |
| Treatments                   | Commercial carpet soil protection & static control   |
| Broadloom Adhesive           | Totally Premium Broadloom Adhesive   |
| Tile Adhesive                | Totally Premium Tile Adhesive  |
| Flammability                 | Passes Class 1 (ASTM E-648)  |
| Electrostatic Propensity     | Passes AATCC - 134 @ 3.5 KV or less  |
| Dye Lot Size                 | Unlimited  |
| Custom Colors & Weight       | Please Inquire   |
| Origin                       | Made in USA  |
| LEED                         | Contributes to Leed Credits  |
| CRI                          | Green Label Plus   |
| Warranty                     | Tile: limited lifetime warranty.<br>Broadloom: 10 year limited warranty  |

