



Totally Carpet Specs

Style Name	Today Shear
Style Number	1041
Pattern Repeat	0.4"W x 0.44"L
Tufted Yarn Weight	46 oz
Gauge	1/10
Construction	Tip Sheared
Face Yarn	100 % Solution Dyed Nylon
Yarn Spec	Cortex™ Twisted & Heatset for High Performance
Tufts/sq in.	180 (Gauge x Stitch Rate x Tufts/Stitch)
Pile Height	0.125
Primary Backing	4 oz Woven Polypropylene
Secondary Backing	High Performance Backing System with 18x5 Lino ActionBac
Tile Backing	Vinyl composite with recycled content
Width Broadloom	12'
Tile Size	24" x 24"
Treatments	Commercial carpet soil & static control
Post Installation Protection	Plastic protection is prohibited. It causes discoloration and accelerated soiling. Craft paper, corrugated box material or masonite are recommended.
Recommended Adhesive Broadloom	Totally Premium Broadloom Adhesive
Recommended Adhesive Tile	Totally Premium Tile Adhesive
Flammability	Passes Class 1 (ASTM E-648)
Electrostatic Propensity	Passes AATCC - 134 @ 3.5 KV or less
Dye Lot Size	Unlimited
Custom Color & Weight	Please Inquire
Origin	Made in USA
LEED	Contributes to Leed Credits
CRI	Green Label Plus
Warranty	Tile: Limited lifetime warranty Broadloom: 10 year limited warranty